

# Evo EVent™ 48E

DESIGNED FOR FRONT-OF-HOUSE DISPLAY COOKING

## Certified Ventless

Can be placed anywhere, no overhead hood or ducting required due to completely self-contained four-stage filtration system

## Digital Controls

Resistive interactive touchscreen display that provides instant status of filters, grease drawers, and control of temperature presets

## Menu Flexibility

Variable temperatures from 100°F-550°F (EVent™ 48E) and 100°F-425°F (EVent™ 48E Plus)



## Electric

Incredibly responsive while reducing the carbon footprint in commercial kitchens

## Versatile

Features 24" x 48" rectangular steel cook surface with a heat-focused center (EVent™ 48E) or edge-to-edge cooking (EVent™ 48E Plus)

## Built-in Fire Suppression

Nozzles in cross-pattern arrangement provide a continuous zone of protection

INNOVATION FROM

# evo

evoamerica.com | sales@evoamerica.com  
866.626.1802



Scan for  
a 360°  
tour

© 2023 Evo America, LLC



# evo

## Four-stage Filtration System

**Stage 1**



An internal stainless steel grease filter captures airborne grease. This metal filter is washable.

**Stage 2**



An aluminum mesh filter captures airborne food particles. This metal filter is washable.

**Stage 3**



An electrostatic precipitator filter further extracts airborne grease, and smoke particles. This metal filter is washable.

**Stage 4**



The last filter is a disposable activated charcoal post-filter.




**DISPLAY COOKING**

- Engage Customers
- Focus on Freshness
- Enhance Convenience
- Realize Higher Margins
- Increase Prepared Food Offerings

**SMART HEAT™ TECHNOLOGY**

Consistent, responsive and quick recovery are critical needs in commercial kitchens.

Our Smart Heat™ Technology allows for even heat and quick temperature recovery times utilizing four (EVent™ 48E) or six (EVent™ 48E Plus) heaters that are energized sequentially.



Single heater shown

**PERFECT FOR**

- Chain Restaurants
- Stadiums and Arenas
- Cafeterias
- Convention Centers
- Grocery Stores
- Foodservice Operators

Electrical Connection	Model	Voltage	Phase	Dedicated Circuit	Plug
	EVent 48E	208-240V, 60 Hz	1 Phase	40A	NEMA 6-50P
	EVent 48E Plus	208V, 60 Hz	3 Phase	40A	NEMA 15-50P

Due to ongoing product improvement, specifications are subject to change without notice.